

EMERGENCY AND FIRST AID PROCEDURES:

Skin: Immediately flush area with plenty of water. If skin feels slippery, alkali may still be present. Continue washing until slick feeling is gone. If irritation persists, obtain medical attention.

Eyes: Immediately flush eyes with plenty of water for 15 minutes. If irritation persists, seek medical attention.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration, preferably mouth to mouth. If breathing is difficult, give oxygen. Contact a physician.

Ingestion: Consult a physician.

SECTION 06 - CORROSIVITY AND REACTIVITY DATA

Stability: Stable

Incompatibility: Do not mix with acids and strong oxidizing agents.

Hazardous Decomposition: Oxides of carbon and nitrogen

Hazardous Polymerization: Will not occur

SECTION 07 - STORAGE, HANDLING, AND USE PROCEDURES

Normal Storage and Handling: Normal warehouse procedures.

Normal Use: Normally used as a 2-4% solution in vibratory or tumbling equipment. Normal use does not present respiratory or ingestion hazard.

Steps to be taken in case of leaks or spills: Flush with water or soak up with inert material and shovel into container.

Waste Disposal Method: Dispose of in accordance with federal, state and local laws.

SECTION 08 - PERSONAL PROTECTION INFORMATION

Respiratory Protection: Use NIOSH/MSHA approved filter respirator for routine work purposes when exposure to dust or mists exceed the permissible exposure limits.

Ventilation: Local exhaust sufficient to maintain dust or mist levels below permissible exposure limits.

Protective Gloves: Impervious type

Eye Protection: Chemical splash goggles.

Personal Hygiene: Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Promptly remove soiled clothing and wash thoroughly before reuse.

Measures To Be Taken During Repair And Maintenance Of Contaminated Equipment That Has Been In Contact With This Material: See Sections 07 and 08.

SECTION 09 - SPECIAL PRECAUTIONS

Precautions to be taken in handling and storage: Store in cool dry area.

FOR COMPANY USE

The information and recommendations set forth herein are taken from sources believed to be accurate as of the date hereof; however, Precision Finishing Inc., makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.