

THE J.S. McCORMICK COMPANY
MATERIAL SAFETY DATA SHEET
PAGE 1 OF 3

Users may consult OSHA and other applicable safety laws/regulations before use.

PRODUCT NAME: L-340 JET SHOT

Date mailed:

Date of last revision: 2/1/08

SECTION ONE -- SOURCE AND NOMENCLATURE

Manufacturer: The J.S. McCormick Company
Address: 1043 Branchton Road
City, St., Zip: Boyers, PA 16020-6682
Emergency Phone: (724) 794-6356

Chemical Name and Synonyms: metallurgical Coke, CAS Number 65996-77-2
Chemical Family: NA
Intended Uses: Additives

SECTION TWO -- HAZARDOUS INGREDIENTS

<u>Ingredient in Product</u>	<u>%</u>	<u>PEL</u>	<u>TLV</u>	<u>Other Work Place Exposure Limits</u>
Carbon 65996-77-2	100		10 mg/m ³	

Remarks:

SECTION THREE -- PHYSICAL DATA

	<u>Entire Product</u>	<u>Or Ingredient (Name)</u>
Boiling Point (F):	NA	NA
Melting Point (F)(Give Method):	NA	NA
Specific Gravity (Water = 1):	1.8 - 2.1	NA
Vapor Pressure (mmHg):	NA	
Evaporation Rate:	NA	
Vapor Density (Air = 1):	NA	
Percent Volatile:	(Volume) NA	(Weight) ND
Other:	NA	
Appearance/Odor:	Black Granular / None	

SECTION FOUR – FIRE AND EXPLOSION HAZARD DATA

Flash Point: ND
Method Used: ND
Flammable Explosive Limits: (Name) ND (Lower) ND (Upper) ND
Fire Extinguishing Media: Water, CO2, Dry chemical, Foam
Special Fire Fighting Procedures: For uses intended the material will not support combustion. Although the material will support combustion at temperatures exceeding 1400 Deg F.
Unusual Fire and Explosion Hazards: Rapid combustion of air borne dust may be started by high temperature ignition source (flame or surface above 1400 Deg F, etc.)

SECTION FIVE – PRODUCT HEALTH HAZARD DATA

Routes of entry: Inhalation, Swallowing, Eyes
Possible Symptoms of Exposure

Eyes: Irritation

Skin: Irritation

Breathing: Cough, shortness of breath.

Ingestion: ND

Other: ND

Chronic Effects: Repeated inhalation of dust in excess of TLV over an extended period of time may result in injury to lungs.

Emergency and First Aid Procedures

Inhalation: Remove from area of exposure.

Skin contact: Wash with soap and water.

Eye contact: Flush with water for at least 15 minutes. Contact physician.

Ingestion: Contact physician.

Other: Contact physician.

SECTION SIX – REACTIVITY DATA

Stability: Stable

Incompatibility (Materials to avoid): Avoid contact with strong oxidizers.

Hazardous Decomposition Products: ND

Hazardous Polymerization: Will not occur.

SECTION SEVEN - SPILL OR LEAK PROCEDURES

Steps to be taken if material is released or spilled:

All cleanup of dry product or dust to be performed by vacuum and/or wet cleaning methods.

Waste disposal method:

Disposal must be carried out in accordance with local, state and federal regulations.

SECTION EIGHT - SPECIAL PROTECTION INFORMATION

Ventilation Requirements:

Use adequate ventilation in volume and pattern to keep concentration in air below TLV or PEL.

Protective Equipment:

Eyes - Comply with OSHA standard 1910.133.
Gloves - As required to prevent excessive contact.
Respiratory - Comply with OSHA standard 1910.134.

Other Protective Equipment:

Comply with OSHA standard 1910.132.

Shipping Methods:

Ground, Air and Sea Non-Hazardous

SECTION NINE - SPECIAL PRECAUTIONS

Handling/Storage Precautions:

Avoid broken or punctured drums to prevent spillage and excessive concentration in air.

Other Precautions:

Avoid prolonged breathing of dust or mist. Use only with adequate ventilation. Avoid contact with skin and eyes.

The foregoing data has been compiled from sources, which the company, in good faith, believes to be dependable, and is accurate and reliable to the best of our knowledge and belief. However, the company cannot make any warranty or representation respecting the accuracy or completeness of the data and assumes no responsibility for any liability or damages relating thereto or for advising you regarding the protection of your employees, customers or others.

ND - Not Determined

NA - Not Applicable

< Less Than

> More Than