

BLAST-IT-ALL Model 4836P




General Information

4836P Cabinet with Reclaimer and Dust Collectors


Model Number	Reclaimer/CFM	Dust Collector	Estimated Shipping Weight (lbs)	Floor Area Required (W)	Floor Area Required (D)
4836-7P	700	Bag	1000	117"	96"
4836-7PDC	700	D10 DC	1200	117"	96"
4836-7PM2DC	700	M2DC	1280	117"	102"
4836-9P-3	900	2 Bags	1350	117"	102"
4836-9PDC-3	900	D20 DC	1550	117"	102"
3636-9P-M4DC-3	900	M4DC	1650	117"	102"
3636-9P-RPJ2	900	RPJ(Dust Drawer)	1650	117"	102"
3636-9P-RPJH2-3	900	RPJ(Dust Hopper)	1690	117"	102"

Door Opening



Floor Area Required Shown With 700 CFM Reclaimer

A B C D E
33" 40" 19" 15" 25"



Reclaimer and Dust Collector

Cabinet Construction:

14 Gauge Reinforced Continuously Welded
45 Degree Minimum Sump Media Flow

Finish:

Durable Enamel
Primed and Painted. Corrosion Resistant

Working Chamber:

Dimensions: 48"W x 36"D x 42"H
Double Walled Doors
Safety Door Interlocks
Self Adjusting Door Latches
Knife Edge, Self Sealing, Full Gaskets
Full Length Hinges

Viewing Window:

12.5"H x 21"W
Quick Change, Square Cornered, Tempered
Glass

Lighting:

Dual, Two-Tube, 24" Fluorescent Fixture Low Temperature, Shielded, Externally Located
120 V 60 Hz

Full Width Foot Treadle:

For instant Changing From Right to Left Foot
On/Off Air Logic Controls

Media Blasting Gun:

Lightweight Aluminum Pistol Grip,
5/32" Air Orifice Standard
4/32", 6/32", 7/32' Orifices Optional
Operated Right or Left Handed

Air Requirements (CFM) 40 PSI 60 PSI 80 PSI

3/16" nozzle	21	32	41
1/4" nozzle	41	56	72
5/16" nozzle	64	88	113

Gloves:

Abrasive Resistant, Cloth Lined, Full Length Snap-In, Static Resistant Gauntlet

Hoses:

1/2" ID. Lightweight, Flexible, Abrasive Resistant

Blow-Off Gun:

Fingertip Control Blow Off Nozzle

